



Product description:

This product is based on strong cleaning solvents. The feature of this product is fast performance and excellent paint cleansing power.

Application:

This product is used to clean the paint from all surfaces .

Technical data:

Specification	Details	EN Standard	ASTM Standard
Appearance	Viscose liquid	Visual	Visual
Working Time (Pot Life)	60-30 minutes		

Environmental Conditions:

This product can be run at 5 - 35°C on dry place.



ALKYD PAINT – PAINT CLEANER (PR- 111)

Surface Preparation:

Apply this product to the desired amount on the surface free of any contamination and fat. .

Method of Applying:

No need to heat or dilute, apply the paint eraser with the appropriate thickness with brush on the surface.

Safety Tips:

This coating is flammable and should be away from flame and heat and also the executor is obliged to observe the MSDS conditions of the product.

Storage Conditions:

This coating is flammable and should be away from flame and heat and also the executor is obliged to observe the MSDS conditions of the product.

packing:

Quart (Metal can)

Galon (Metal can)

Considerations:

The available information is based on our technical knowledge and laboratory research, but since the conditions and methods of application are different and out of reach, we do not guarantee the results of it.

LEGAL NOTES : : The information contained in this Technical Data Sheet is based on laboratory testing and practical experience. Actual performance may vary depending on substrate condition, application method, and environmental conditions. Users should test suitability before large-scale application.

Head Office : Building No.15 , Qasimlu Street 40, Shahidan Zargata Quarter 24, Zone 1, Sulaymaniyah 46001, Iraq

Factory : Tanjaro Industrial Area – Sulaymaniyah – Iraq