

**CHEMICAL CONSTRUCTION- REMOVE THE PAINT (PR-111)****Product description:**

This product is based on strong cleaning solvents. The feature of this product is fast performance and excellent color cleaning power.

Application:

This product is used to remove paint from all surfaces

Technical data:

Specification	Details	EN Standard	ASTM Standard
Appearance	Viscous liquid	Visual Inspection	Visual Inspection
Performance	30 to 60 Min	-	-

Equipment Used:

Brushes are suitable for applying this coating.

Environmental Conditions:

This product can be applied at a temperature of 5 - 35° c on a dry surface.

**Method of Applying:**

Without heating or diluting, apply the paint remover with a suitable thickness with a brush on the surface.

Safety Tips:

This product is water-based and non-flammable. But it is recommended that in case of skin contact, wash it with soap and large amounts of water and consult a doctor in case of skin sensitivity and irritation.

packing:

5 kg (bag)

25 kg (bag)

Storage Conditions:

It should be kept in a closed environment with proper ventilation at a temperature of (5-35°C) for 2 years.

Considerations:

The available information is based on our technical knowledge and laboratory research, but since the conditions and methods of application are different and out of reach, we do not guarantee the results of it.

Surface Preparation:

The surface must be clean, dry and free from any contamination. If there are old colors, sand the surface and then apply.

LEGAL NOTES : The information contained in this Technical Data Sheet is based on laboratory testing and practical experience. Actual performance may vary depending on substrate condition, application method, and environmental conditions. Users should test suitability before large-scale application.

Head Office : Building No.15 , Qasimlu Street 40, Shahidan Zargata Quarter 24, Zone 1, Sulaymaniyah 46001, Iraq

Factory : Tanjaro Industrial Area – Sulaymaniyah – Iraq