



WOOD ALKYD PAINT – INSTANT THINNER (SOLVE - 220)

Product description:

This product is based on nitrocellulose resin.

Application:

The mentioned thinner has fast drying time, excellent cutting viscosity, without affecting asphalt and cement surfaces, and for diluting colors based on nitrocellulose is used.

Technical data:

Specification	Details	EN Standard	ASTM Standard
Sheen (Gloss Level)	Clear	EN ISO 2813	D523
Density / Specific gravity g/cm ³	at 25° C: 0.8-0.9 gr/cm ³	EN ISO 2811	D1475
Boiling Point (Solvent) °C	56 - 142		

The drying time depends on the thickness of the applied film, the ambient temperature, the humidity of the environment and the wind flow. All information in this catalog is based on dry film thickness in laboratory conditions.

packing:

Gallon (Metal Can)

Storage Conditions:

It should be stored in an open space and away from direct sunlight at a temperature of 5-35 °C. Our guarantee is the storage time of the product for 1 years.

Considerations:

The available information is based on our technical knowledge and laboratory research, but since the conditions and methods of application are different and out of reach, we do not guarantee the results of it.

Safety Tips:

This cover is flammable and should be kept away from flame and heat.

Also, the operator is obliged to study and comply with the MSDS conditions of this product, use a special mask and safety gloves while using it, and perform the operation in an environment with proper ventilation.

LEGAL NOTES : : The information contained in this Technical Data Sheet is based on laboratory testing and practical experience. Actual performance may vary depending on substrate condition, application method, and environmental conditions. Users should test suitability before large-scale application.

Head Office : Building No.15 , Qasimlu Street 40, Shahidan Zargata Quarter 24, Zone 1, Sulaymaniyah 46001, Iraq

Factory : Tanjaro Industrial Area – Sulaymaniyah – Iraq